


# CM8V-T1A

## Tuning Fork Crystal 32.768 kHz



### DIMENSIONS



### APPLICATIONS

IoT  
 Metering  
 Industrial  
 Automotive  
 Health Care  
 Wearables, Portables

### DESCRIPTION

The CM8V-T1A is a low frequency SMT Quartz Crystal Unit that incorporates a tuning fork Quartz Crystal Resonator. It operates under vacuum in a hermetically sealed ceramic package with metal lid.

### FEATURES

Ultra small size, low profile, lightweight (4.6 mg).  
 Outstanding hermetic sealing with gold-tin preform.  
 High stability and low aging guaranteed by hermetic sealing.  
 Available for extended operating temperature range.  
 High shock and vibration resistant.  
 100% Pb-free, RoHS-compliant.  
 Automotive qualification according to AEC-Q200 available.

### ELECTRICAL CHARACTERISTICS AT 25°C

Standard Frequencies 32.768 kHz / 100.000 kHz	<sup>1)</sup> F <sub>L</sub>	32.768	kHz
Load capacitance	<sup>2)</sup> C <sub>L</sub>	4.0 / 6.0 / 7.0 / 9.0 / 12.5	pF
Frequency tolerance	<sup>3)</sup> ΔF/F	±20	ppm
		±100	ppm
Series resistance typ./max.	R <sub>S</sub>	55 / 75	kΩ
Motional capacitance typ.	C <sub>1</sub>	4.0	fF
Static capacitance typ.	C <sub>0</sub>	1.2	pF
Drive level max.	P	0.5	μW
Insulation resistance min.	R <sub>i</sub>	500	MΩ
Aging first year max.	ΔF/F	±3	ppm
Turnover temperature	T <sub>0</sub>	25 ±5	°C
Frequency vs. temperature	ΔF/F <sub>0</sub>	-0.035 ppm/°C <sup>2</sup> (T - T <sub>0</sub> ) <sup>2</sup> ±10%	

- 1) Other frequencies on request.  
 2) Other load capacitances on request.  
 3) Tighter frequency tolerances on request.

**STANDARD FREQUENCIES**

Frequencies
32.768 kHz / 100.000 kHz
Other frequencies on request

**ENVIRONMENTAL CHARACTERISTICS**

		Conditions	Max. Dev.
Storage temp. range		-55 to +125°C	
TA Operating temperature range		-40 to +85°C	
TB Extended oper. temp. range		-40 to +125°C	
TC Extended oper. temp. range		-55 to +125°C	
Shock resistance	ΔF/F	5000 g, 0.3 ms, ½ sine	±5 ppm
Vibration resistance	ΔF/F	20 g / 10–2000 Hz	±5 ppm

**TERMINATIONS AND PROCESSING**

Type	Termination	Processing
CM8V-T1A	For SMT mounting Au flashed pads	IPC/JEDEC J-STD-020C 260°C / 20 - 40 s

**ORDERING INFORMATION**

CM8V-T1A 32.768 kHz 12.5 pF ±20 ppm TA QC	
Ceramic package	Frequency $F_L$
Metal lid	Load capacitance $C_L$
Package size	4.0 pF, 6.0 pF
8 = 2.0 x 1.2 x 0.6 mm	7.0 pF
Tuning fork	9.0 pF
SMT Package	12.5 pF
Au flashed pads	Other $C_L$ on request
Pads on both ends	Frequency tolerance
	±20 ppm
	±100 ppm
	Tighter freq. tolerances on request
	Temperature range
	TA = -40 to +85°C (Standard)
	TB = -40 to +125°C
	TC = -55 to +125°C
	Qualification
	QC = Commercial Grade (Standard)
	QA = Automotive Grade AEC-Q200

A unique part number will be generated for each product specification, i.e:	
20xxxx-MC01	1'000 pcs (in 8 mm tape on 7" reel)
20xxxx-MC03	3'000 pcs (in 8 mm tape on 7" reel)

All specifications subject to change without notice.

